

Datasheet Conveyor Belt



**NITTA CORPORATION
OF HOLLAND**

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:**
1 LRFP 06/W2 IM
- **Nitta Japan code:**



Construction: 1 ply polyester, rigid

	TOP COVER	INNER LAYER	BOTTOM SIDE	
Material:	PU	-	Impregnated fabric	
Thickness:	0,6			mm (approx.)
Colour:	White	Not applicable		
Hardness:	87 Shore A			
Profile:	-			

Total thickness:	1,1	mm (approx.)
Weight:	1,2	kg/m ² (approx.)
Max. width:	3000	mm
Belt support:	Sliderbed (Rollers), Flat	

Rating at 1% elongation:	4	N/mm
Advised pretension:	2 - 3	N/mm
Maximum allowable tension:	7	N/mm
Temperature range:	-20 to +80	°C

Minimum pulley diameters:		
Flexing:	6 - 8	mm
Backflexing:	20	mm

Special approval: FDA, 10/2011/EC + amendments

Applications:

- Biscuit bakeries
- Cutting belt on dough production lines
- Depanner belt for bread bakeries
- Oil and grease resistant

Date of issue 11-12-2014-2

Your Partner In Belting Solutions

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nittacorporation.com