

Datasheet Conveyor Belt



**NITTA CORPORATION
OF HOLLAND**

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:**
2 RF 72 IM 55°
- **Nitta Japan code:**



Construction: 2 plies polyester, rigid

	TOP COVER	INNER LAYER	BOTTOM SIDE	
Material:	PVC	PVC	Impregnated fabric	
Thickness:	2		-	mm (approx.)
Colour:	White	White	-	
Hardness:	55 Shore A		-	
Profile:	-		-	

Total thickness:	3,75	mm (approx.)
Weight:	4,6	kg/m² (approx.)
Max. width:	3000	mm
Belt support:	Sliderbed (Rollers), Flat	

Rating at 1% elongation:	10	N/mm
Advised pretension:	4 - 7	N/mm
Maximum allowable tension:	20	N/mm
Temperature range:	-10 to +90	°C

Minimum pulley diameters:		
Flexing:	60	mm
Backflexing:	140	mm

Special approval: FDA, 10/2011/EC + amendments

Applications:
 Conveyor belt for the food industry
 Conveying of meat, fish and poultry products
 In the dairy and bakery industry
 Oil and grease resistant

Date of issue 02-07-2014-1

Your Partner In Belting Solutions

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nittacorporation.com